




TECHNICAL DATA				
	Units	Ratio	RAAS	RLAS
Available Ratios	-		1,2,3,4,5	2,3,4,5
Nominal Output Torque	Nm	1	25.5	-
		2	24.5	
		3	21.3	
		4	20.4	
		5	18	
Max. Ouput Torque		1 - 5	nominal x2	
Emergency Stop Torque		1 - 5	nominal x2.5	
Nominal Input Speed	RPM	1 - 5	4,000	
Max. Input Speed			6,000	
Input Shaft Moment of Inertia	kg-cm^2	1	0.36	-
		2	0.23	
		3	0.21	
		4	0.21	
		5	0.20	
Max. Axial Load	N	1 - 5	815	635
Max. Radial Load		1 - 5	1630	1270
Torsional Stiffness	Nm/arcmin	1	4.3	-
		2	4.1	
		3	3.6	
		4	3.4	
		5	3.0	
Efficiency at Full Load	%	1 - 5	95≤	
Avg. Service Life	Hrs	1 - 5	20,000	
Weight	Kg	1 - 5	1.9	1.7
Backlash	arcmin	1 - 5	≤6	
Noise Level*	dB	1 - 5	≤70	
Protection Rating	IP rating	1 - 5	64	
Operating Temp.	°Celcius	1 - 5	-20 to 100	



Note: RAAS-060-00 □ model shown



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MYOSTAT MOTION CONTROL INC.
ANY REPRODUCTION IN PART OR AS A
WHOLE WITHOUT THE WRITTEN PERMISSION
OF COOLMUSCLE INC. IS PROHIBITED.



Myostat Motion Control Inc.
+1 905-836-4441
www.myostat.ca